



SPECIAL FEATURES

SINGLE PORT INSTALLATION FOR PRESSURE AND TEMPERATURE MEASUREMENT
COST EFFECTIVE
EXCELLENT FOR HVAC INDUSTRY
RUSTPROOF DESIGN

SPECIFICATIONS

STANDARD VERSION : 100 mm

Accuracy	1.6
Case & bezel	ABS flastic
Pressure element	Bourdon (Copper alloy)
Temperature element	Bi-metal strip coiled
Connection	AISI 304 SS
Stem diameter	6 mm (standard)
Stem material	AISI 316 SS
Pointer	Aluminium, black coloured.
	For Temp. = slotted & for pressure = fixed
Dial	Aluminium, black graduation on white background.
Movement	Copper alloy

HOW TO ORDER

BASIC MODEL

CODE

MOUNTING

4 DIRECT CENTER BACK ENTRY

PROCESS CONNECTION

3BM 3/8" BSP (M) STANDARD 3JM 3/8" PF (M)

STEM LENGTH [Below threads]

Please specify in mm (Stem length 65 mm to 150 mm)

PRESSURE RANGE in Kg/cm²

06 0 to 6 07 0 to 7 10 0 to 10 16 0 to 16 21 0 to 21 25 0 to 25 40 0 to 40

TEMPERATURE RANGE in °C

50 0 to 50 °C 100 0 to 100 °C 150 0 to 150 °C

OPTIONAL EXTRAS

RH CUSTOM DESIGNED DIAL SX SS TAG PLATE
PW FIVE POINT CALIBRATION CERTIFICATE SW DIAL TAG MARKING

Ordering Example: T-04 - X - XXX - 100 mm - XX - XX - XX

FOR OTHER OPTIONAL ITEMS, PLEASE CONTACT FACTORY FOR DELIVERY AND MINIMUM QUANTITY OF ORDER.

Example

T-04

X

XXX

100 mm

XX

XX

XX